

Ce document vous est fourni par Supratec ENOMAX Partenaire officiel de Finn.Power en France www.supratec-enomax.com



VERSION 2.3

CM91

Finn-Power CM91 hose-cutting machine has been designed to cut up to 3" hoses.

The hose is pushed against the blade by a electrical pusher.

Electrical pusher movement adjusts pusher speed automatically providing optimal cutting speed for every hose and preventing blade overheating.

A0 0A

The blade can be sharpened when necessary. The cutter has a built-in bin for collecting cutting waste.

SAFE-model also available.

TECHNICAL DATA		
Max. hose size (inch)	3	
Diameter (blade) external (mm)	650x4	
Diameter (blade) internal (mm)	42	
Max. hose OD (mm)	120	
Exhaust outlet OD (mm)	125	A SING OF
Motor Power (kW/HP)	11.0 / 15.0	No. of Contraction of
Velocity, 50Hz (rpm)	2900	Toothed blade
/elocity, 60Hz (rpm)	3480	
DIMENSIONS (LxWxH)		
mm	1400x967x1614	
nch	55.1x38x63.5	
WEIGHT		PINN-PO
kg/lbs	275/605	Smooth blade

ABSOLUTE/ QUALITY ∕IADE IN FINLAND

STANDARD FEATURES

Touchscreen Toothed blade (part no 705179) Foot pedal Adjustable electric pusher speed Adjustable hose support Mechanical safeguard

OPTIONS

Measuring table (1,5 m segments) (part no 705605) Fume extractor (part no 720460) Smooth blade (part no 706298)



Touchscreen as standard feature

