

## P2OSCC

Finn-Power P2OSCC is strong, fast and reliable crimping machine for any service crimping need.

This model turns hydraulics off to conserve energy, and to reduce workplace noise levels whenever the machine is idle.

SCC control brings smartness to workshop crimpers via connectivity and visual user interface, including step crimping as a standard feature. Optional single foot pedal can be connected to workshop SCC models.


TECHNICAL DATA			
Max crimping dia (mm) 1)	61		
Max crimping dia (inch) 1)	2.40		
Max crimping force (kN)	1370		
Max crimping force (tonnage)	137		
Cycle time 10 mm (s) <sup>2) 3)</sup>	3.6/10.3		
Hose size ID (inch)	1 ½ *		
Die set series	20		
Max opening (mm) 4)	+25		
Max opening without dies (mm)	109		
Master die D/L (mm)	84/80		
Master die D/L (inch)	3.31/3.15		
Motor Power (kW/HP) <sup>3)</sup>	3.0/4.0 1.5/2.0		
Oil tank volume	27		
DIMENSIONS (LxWxH)			
(mm)	650x510x757		
(inch)	25.6x20.1x29.8		



137/309

\* ACCORDING TO THE FITTING.

FURTHER INFO ON PRODUCTS, PLEASE REVERT TO SPECIFIC PRODUCT CARD



- With standard dies. Crimping range can be increased with special dies. Theoretical with 10 mm cycle. 1)
  - 3-phase/1-phase
- 3) 4) 3-pnase/1-pnase Maximum opening is the total die travel. Add this value to the minimum crimping diameter of the die set used. The result is the maximum opening of the machine with die set in place.

CONTROL	
SCC (5" touchscreen)	)

## OPTIONS

Foot pedal

Mechanical back stop device Electrical back stop device Tool base (20 slots) with QuickChange-tool

Tool rack (12 slots) with QuickChange-tool







Tool base and Tool rack with QuickChange-tool as an option.

		CDICO
E SEI	20-5	<b>ERIES</b>

DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
18013/10	10	55	10.0-12.0
18013/12	12	55	12.0-14.0
18013/14	14	55	14.0-16.0
18013/16	16	55	16.0-19.0
18013/19	19	55	19.0-23.0
18013/23	23	55	23.0-27.0
18013/27	27	70	27.0-31.0
18013/31	31	70	31.0-36.0
18013/36	36	75	36.0-41.0
18013/41	41	75	41.0-47.0
18013/47	47	85	47.0-54.0
18013/54	54	85	54.0-61.0

In addition to the standard die sets, a wide range of special die sets is available on request.



